

CAPRI

Φ114 Hat Pendant



Fixed Optic



Ceiling hook to move light point



White Painted



Black Painted



cutout:58mm

Ø62.5

17.5

1200

Ø114

Recessed Trim



Ø50


84

1200


Ø114

Surface

IP Rating:	IP20
Optics:	10°/24°/36°/55°
UGR:	< 10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K/2000K-3000K/1800K-4000K/2700K-6500K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W
Ambient temp:	-20 C to 45 C
Class:	II



W system	lm system	optics	code
6W	376	10°	PJRT11406W-30N10-SG
6W	597	24°	PJRT11406W-30N24-SG
6W	590	36°	PJRT11406W-30N36-SG
6W	545	55°	PJRT11406W-30N55-SG



W system	lm system	optics	code
8W	445	10°	PJRT11408W-30N10-SG
8W	738	24°	PJRT11408W-30N24-SG
8W	736	36°	PJRT11408W-30N36-SG
8W	672	55°	PJRT11408W-30N55-SG



W system	lm system	optics	code
6W	376	10°	PJST11406W-30N10-SG
6W	597	24°	PJST11406W-30N24-SG
6W	590	36°	PJST11406W-30N36-SG
6W	545	55°	PJST11406W-30N55-SG



W system	lm system	optics	code
8W	445	10°	PJST11408W-30N10-SG
8W	738	24°	PJST11408W-30N24-SG
8W	736	36°	PJST11408W-30N36-SG
8W	672	55°	PJST11408W-30N55-SG