


LINE

LED STRIP GENERAL



Fixed Optic



Accessories not included



Fast Connector (FC1010)

IP Rating:	IP20
Optics:	120°
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Voltage:	DC 24V
Power(W):	3.6W/m, 6W/m, 7.2W/m, 9.6W/m, 12W/m, 15W/m
LEDs/m:	120
Min. Cut Length:	50mm
Ambient temp:	-20 °C to 45 °C
Class:	III



W system	lm system	optics	code
3.6W	103lm/W	120°	GS2835-120-3.6W-24



W system	lm system	optics	code
6W	103lm/W	120°	GS2835-120-6W-24



W system	lm system	optics	code
7.2W	90lm/W	120°	GS2835-120-7.2W-24



W system	lm system	optics	code
9.6W	90lm/W	120°	GS2835-120-9.6W-24



W system	lm system	optics	code
12W	90lm/W	120°	GS2835-120-12W-24



W system	lm system	optics	code
15W	90lm/W	120°	GS2835-120-15W-24