


BELLA 48V

Φ41 Zoomable 20°-50° 48V Track Light




Adjustable Optic




-  White Painted
-  Black Painted
-  Antique Bronze
-  Brushed Grey

- IP Rating:** IP20
- Optics:** Zoomable 20°-50°
- UGR:** <17
- CRI:** 92Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 3000K/3500K/2700-6000K
- Typical Source**
- Efficacy (lm/W):** 96
- Control:** On/off, 0/1-10V, Dali, Zigbee, Casambi
- Binning:** 2 Step MacAdams
- Input:** 48 VDC
- Output:** 12V 600mA 8W
- Ambient temp:** -20 C to 45 C
- Class:** III
- Material:** structure fine aluminum 6063A




8W Ra92 3000K 20°

h(m)	E(lx)	D(m)
0.5	2978	0.21
1.0	745	0.42
1.5	331	0.63
2.0	186	0.84
2.5	119	1.04
3.0	83	1.25



8W Ra92 3000K 30°

h(m)	E(lx)	D(m)
0.5	1805	0.30
1.0	451	0.59
1.5	201	0.89
2.0	113	1.18
2.5	72	1.48
3.0	50	1.78



8W Ra92 3000K 50°

h(m)	E(lx)	D(m)
0.5	795	0.49
1.0	199	0.97
1.5	88	1.46
2.0	50	1.94
2.5	32	2.43
3.0	22	2.91



W system	lm system	optics	code
8W	388-385	20°- 50°	MT4108W-30N2050-B