

ACME

75 X 75


Outdoor Wall Light




Fixed Optic



Black Painted




IP Rating:	IP65
Optics:	15°/24°/36°/50°
UGR:	<10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	3000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 250mA 10Wx2
Ambient temp:	-20 C to 45 C
Class:	II
Optional accessories:	Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter
Material:	Fine aluminium 6063A




10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	11475	0.15
1.0	2869	0.30
1.5	1275	0.45
2.0	717	0.60
2.5	459	0.76
3.0	319	0.91




10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	6198	0.22
1.0	1550	0.44
1.5	689	0.67
2.0	387	0.89
2.5	248	1.11
3.0	172	1.33



10W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	3390	0.31
1.0	847	0.62
1.5	377	0.92
2.0	212	1.23
2.5	136	1.54
3.0	94	1.85



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	1133	0.49
1.0	283	0.98
1.5	126	1.47
2.0	71	1.96
2.5	45	2.45
3.0	31	2.94



W system	lm system	optics	code
10Wx2	553x2	15°	OWQE6810Wx2-30N15-B
10Wx2	575x2	24°	OWQE6810Wx2-30N24-B
10Wx2	565x2	36°	OWQE6810Wx2-30N36-B
10Wx2	485x2	50°	OWQE6810Wx2-30N50-B