

GLAMO

Φ68 Recessed Zoomable 15°-50° Spotlight




Adjustable Optic




 Black Painted



Recessed Trim




Recessed Trimless




IP Rating: IP20
Optics: Zoomable 15°-50°
UGR: <17
CRI: 98Ra
Lifetime: >50,000 hrs (L70 B10)
CCT: 2700K/3000K/3500K/4000K/5000K/
 2000K-3000K/1800K-4000K/2700K-6000K

Typical Source Efficacy (lm/W): 110
Control: On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning: 2 Step MacAdams
Input: AC220-240V 50/60Hz
Output: DC 36V 300mA 12W
Ambient temp: -20 °C to 45 °C
Class: II
Material: Fine aluminium 6063A



12W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	12099	0.14
1.0	3025	0.27
1.5	1344	0.41
2.0	756	0.54
2.5	484	0.68
3.0	336	0.81



12W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	2174	0.38
1.0	544	0.76
1.5	242	1.14
2.0	136	1.52
2.5	87	1.90
3.0	60	2.28



DuraGreen project:
YELLOWKORNER Art Gallery



W system	lm system	optics	code
12W	756-747	15°- 50°	RT6812W-30N1550-B



W system	lm system	optics	code
12W	756-747	15°- 50°	TL6812W-30N1550-B