


# ARTFOCUS 48V

Φ36


## Adjustable 48V Track Light



Adjustable Optic



minimal track



standard track




matt white painted




matt black painted

<b>IP Rating:</b>	IP20 and IP44 options
<b>Optics:</b>	15°/28°/36°
<b>UGR:</b>	<10
<b>CRI:</b>	98Ra
<b>Lifetime:</b>	>50,000 hrs (L70 B10)
<b>CCT:</b>	2700K/3000K/3500K/4000K/5000K/ 2000K-3000K/1800K-4000K/2700K-6000K
<b>Typical Source</b>	
<b>Efficacy (lm/W):</b>	110
<b>Control:</b>	On/off, 0/1-10V, Dali, Zigbee, Casambi
<b>Binning</b>	2 Step MacAdams
<b>Input :</b>	48 VDC
<b>Output :</b>	DC 36V 150mA 6W
<b>Ambient temp:</b>	-20 °C to 45 °C
<b>Class:</b>	III
<b>Material:</b>	structure fine aluminum 6063A




6W Ra98 3000K 15°

h(m)	E lx	D(m)
0.5	4937	0.14
1.0	1234	0.27
1.5	549	0.41
2.0	309	0.54
2.5	197	0.68
3.0	137	0.81



6W Ra98 3000K 28°

h(m)	E lx	D(m)
0.5	2848	0.25
1.0	712	0.49
1.5	316	0.74
2.0	178	0.98
2.5	114	1.23
3.0	79	1.47



6W Ra98 3000K 36°

h(m)	E lx	D(m)
0.5	1706	0.31
1.0	426	0.62
1.5	190	0.93
2.0	107	1.25
2.5	68	1.56
3.0	47	1.87



<b>W system</b>	<b>lm system</b>	<b>optics</b>	<b>code</b>
6W	373	15°	TK3606W-30N15-B
6W	445	28°	TK3606W-30N28-B
6W	446	36°	TK3606W-30N36-B