

MOOD


Φ55 Outdoor Downlight




cutout :55mm



Fixed Optic




IP Rating:	IP65
Optics:	10°/24°/36°
UGR:	<10
CRI:	92Ra with 97Ra option
Lifetime:	>50,000 hrs (L70 B10)
CCT:	3000K
Typical Source	
Efficacy (lm/W):	113
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 200mA 8W
Ambient temp:	-20 °C to 45 °C
Class:	II
Optional accessories:	Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter




8W Ra92 3000K 10°

h(m)	E(lx)	D(m)
0.5	7812	0.10
1.0	1953	0.20
1.5	868	0.30
2.0	488	0.40
2.5	312	0.50
3.0	217	0.60



8W Ra92 3000K 24°

h(m)	E(lx)	D(m)
0.5	4392	0.21
1.0	1098	0.43
1.5	488	0.64
2.0	274	0.85
2.5	176	1.06
3.0	122	1.28



8W Ra92 3000K 36°

h(m)	E(lx)	D(m)
0.5	2345	0.32
1.0	586	0.64
1.5	261	0.96
2.0	147	1.28
2.5	94	1.61
3.0	65	1.93



W system	lm system	optics	code
8W	384	10°	WFL5508W-30N10
8W	501	24°	WFL5508W-30N24
8W	517	36°	WFL5508W-30N36