



MOOD MINI

Φ40 Fixed Round




True non-intrusive-in lighting solutions to integrate lighting with architecture

IP Rating:	IP20
Optics:	13°/20°/30°
UGR:	<17
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K
Typical Source Efficacy (lm/W):	103
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 3V 300mA 1.3W DC 3V 650mA 3W
Ambient temp:	-20 C to 45 C
Class :	II




3W Ra92 3000K 13°

h(m)	E(lx)	D(m)
0.5	4168	0.11
1.0	1042	0.23
1.5	463	0.34
2.0	261	0.46
2.5	167	0.57
3.0	116	0.65



3W Ra92 3000K 20°

h(m)	E(lx)	D(m)
0.5	1872	0.18
1.0	468	0.36
1.5	208	0.55
2.0	117	0.73
2.5	75	0.91
3.0	52	1.09




3W Ra92 3000K 30°


h(m)	E(lx)	D(m)
0.5	855	0.25
1.0	214	0.50
1.5	95	0.75
2.0	53	1.00
2.5	34	1.26
3.0	24	1.51



DuraGreen project:
Yue Kai Entertainment Office



W system	lm system	optics	code
1.3W	85	13°	MFL401.3W-30NL13-W
1.3W	98	20°	MFL401.3W-30NL20-W
1.3W	91	30°	MFL401.3W-30NL30-W



W system	lm system	optics	code
3W	165	13°	MFL4003W-30NL13-W
3W	167	20°	MFL4003W-30NL20-W
3W	147	30°	MFL4003W-30NL30-W