

MOOD SQUARE


∅ 68*118 Trimless Adjustable Square



cutout :68*118mm



Adjustable Optic




IP Rating: IP20 and IP44 options
Optics: 10°/24°/36°/50°
UGR: < 10
CRI: 98Ra
Lifetime: > 50,000 hrs (L70 B10)
CCT: 2700K/3000K/3500K/4000K/5000K/
 2000K-3000K/1800K-4000K/2700K-6000K

Typical Source
Efficacy (lm/W): 110
Control: On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning: 2 Step MacAdams
Input: AC220-240V 50/60Hz
Output: DC 36V 150mA 6W*2
 DC 36V 200mA 8W*2
 DC 36V 250mA 10W*2


Ambient temp: -20 °C to 45 °C
Class: II

Optional accessories: Honeycomb louver, Solite Lense, Spread Lense,
 Colour Filter




10W Ra98 3000K 10°

h(m)	E(lx)	D(m)
0.5	8431	0.11
1.0	2108	0.21
1.5	937	0.32
2.0	527	0.43
2.5	337	0.53
3.0	234	0.64



10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	4847	0.21
1.0	1212	0.43
1.5	539	0.64
2.0	303	0.86
2.5	194	1.07
3.0	135	1.29



10W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	2553	0.32
1.0	638	0.65
1.5	284	0.97
2.0	160	1.29
2.5	102	1.61
3.0	71	1.94



DuraGreen project:
London Luxury Home



W system	lm system	optics	code
6W*2	328*2	10°	AFQ6806WX2-TL-30N10-W
6W*2	407*2	24°	AFQ6806WX2-TL-30N24-W
6W*2	417*2	36°	AFQ6806WX2-TL-30N36-W
6W*2	411*2	50°	AFQ6806WX2-TL-30N50-W



W system	lm system	optics	code
8W*2	384*2	10°	AFQ6808WX2-TL-30N10-W
8W*2	501*2	24°	AFQ6808WX2-TL-30N24-W
8W*2	517*2	36°	AFQ6808WX2-TL-30N36-W
8W*2	512*2	50°	AFQ6808WX2-TL-30N50-W



W system	lm system	optics	code
10W*2	411*2	10°	AFQ6810WX2-TL-30N10-W
10W*2	554*2	24°	AFQ6810WX2-TL-30N24-W
10W*2	567*2	36°	AFQ6810WX2-TL-30N36-W
10W*2	558*2	50°	AFQ6810WX2-TL-30N50-W

MOOD



MOOD light fittings, stylishly designed with trendy colors and high-quality materials, radiate sophistication and elegance. They offer endless possibilities and exceptional versatility, easily adapting to any space.





Black Matt



White Matt



Silver Matt



Black Specular



Silver Specular




Gold Specular



Grey Specular

D for DuraGreen Design



Specification Code

Type	Cut out	Power	Colour Temp	Driver	Beam Width	Bezel Colour	Baffle Colour	Options
MF	75	08W	30	N	24	W	B	C
MF/Fixed	22/22mm		27/2700K	M/Mains Dim	05/5°	W/White	B/Black Specular	C/Clear Lens
AF/Adjustable	33/33mm		30/3000K	D/DALI	10/10°	B/Black	S/Silver Specular	F/Frosted Lens
MFL/Lens type, Fixed	35/35mm 40/40mm		40/4000K WD/Warm Dim	0/0-10V N/Non Dim	13/13° 15/15°	L/Polished Chrome G/Polished Brass	W/White Matt BM/Black Matt	H/Honeycomb S/Spread Lense
AFL/Lens type, Adjustable	45/45mm 55/55mm		1840/1800K-4000K 2765/2700K-6500K	X/No Driver	20/20° 24/24°	J/Antique Bronze S/Satin Nickle		
MFW/Wall Wash	58/58mm				30/30°			
MFZ/Zoomable	75/75mm				36/36°			
MFP/Pinhole	80/80mm				50/50°			
MFQ/Fixed Square	100/100mm							