

FLOW


Recessed 6 Spots Linear



cutout :235*48mm



Fixed




White Painted




Black Painted

- IP Rating:** IP20 and IP44 options
- Optics:** 12°/24°/38°/50°/Wall Wash
- UGR:** < 10
- CRI:** 92Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 3000K
- Typical Source Efficacy (lm/W):** 113
- Control:** On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
- Binning:** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 36V 300mA 12W
DC 36V 350mA 15W
- Ambient temp:** -20 °C to 45 °C
- Class:** II




15W Ra92 3000K 24°

h(m)	E(lx)	D(m)
0.5	9378	0.21
1.0	2344	0.43
1.5	1042	0.64
2.0	586	0.86
2.5	375	1.07
3.0	260	1.29



15W Ra92 3000K 38°

h(m)	E(lx)	D(m)
0.5	5017	0.33
1.0	1254	0.67
1.5	557	1.00
2.0	314	1.34
2.5	201	1.67
3.0	139	2.01



15W Ra92 3000K 50°

h(m)	E(lx)	D(m)
0.5	3325	0.50
1.0	831	1.00
1.5	369	1.50
2.0	208	1.99
2.5	133	2.49
3.0	92	2.99



DuraGreen project:
LONGINES Showroom



W system	lm system	optics	code
12W	1075	12°	FFL0612W-30N12-B
12W	1059	24°	FFL0612W-30N24-B
12W	968	38°	FFL0612W-30N38-B
12W	1066	50°	FFL0612W-30N50-B



W system	lm system	optics	code
15W	1187	12°	FFL0615W-30N12-B
15W	1241	24°	FFL0615W-30N24-B
15W	1266	38°	FFL0615W-30N38-B
15W	1220	50°	FFL0615W-30N50-B