

FLOW

Recessed 9 Spots Linear



cutout :350*48mm




Fixed




White Painted



Black Painted




IP Rating:	IP20 and IP44 options
Optics:	12°/24°/38°/50°/Wall Wash
UGR:	< 10
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	3000K
Typical Source Efficacy (lm/W):	113
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 500mA 20W DC 36V 600mA 25W
Ambient temp:	-20 °C to 45 °C
Class:	II




25W Ra92 3000K 24°

h(m)	E(lx)	D(m)
0.5	12084	0.25
1.0	3021	0.50
1.5	1343	0.75
2.0	755	1.00
2.5	483	1.25
3.0	336	1.50



25W Ra92 3000K 38°

h(m)	E(lx)	D(m)
0.5	10063	0.31
1.0	2516	0.61
1.5	1118	0.92
2.0	629	1.22
2.5	403	1.53
3.0	280	1.83



25W Ra92 3000K 50°

h(m)	E(lx)	D(m)
0.5	5483	0.46
1.0	1371	0.92
1.5	609	1.38
2.0	343	1.84
2.5	219	2.30
3.0	152	2.76



W system	lm system	optics	code
20W	1636	12°	FFL0920W-30N12-B
20W	1656	24°	FFL0920W-30N24-B
20W	1584	38°	FFL0920W-30N38-B
20W	1672	50°	FFL0920W-30N50-B



W system	lm system	optics	code
25W	1889	12°	FFL0925W-30N12-B
25W	1883	24°	FFL0925W-30N24-B
25W	1917	38°	FFL0925W-30N38-B
25W	1842	50°	FFL0925W-30N50-B