


DIVINO 48V

Φ35 Adjustable 48V Track Light




 Black Painted




IP Rating: IP20
Optics: 15°/30°/40°/55°
UGR: <10
CRI: 98Ra
Lifetime: >50,000 hrs (L70 B10)
CCT: 2700K/3000K/3500K/4000K/5000K/
2000K-3000K/1800K-4000K/2700K-6000K

Typical Source
Efficacy (lm/W): 110
Control: On/off, 0/1-10V, Dali, Zigbee, Casambi
Binning 2 Step MacAdams
Input: 48 VDC
Output: DC 36V 300mA 12W
Ambient temp: -20 °C to 45 °C
Class: III
Optional accessories: Honeycomb louvre, Solite Lense, Spread Lense,
Colour Filter




12W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	7106	0.14
1.0	1777	0.27
1.5	790	0.41
2.0	444	0.55
2.5	284	0.68
3.0	197	0.82




12W Ra98 3000K 30°

h(m)	E(lx)	D(m)
0.5	3379	0.28
1.0	845	0.56
1.5	375	0.84
2.0	211	1.12
2.5	135	1.40
3.0	94	1.68



12W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	2710	0.38
1.0	678	0.75
1.5	301	1.13
2.0	169	1.50
2.5	108	1.88
3.0	75	2.26



12W Ra98 3000K 55°

h(m)	E(lx)	D(m)
0.5	1235	0.51
1.0	309	1.01
1.5	137	1.52
2.0	77	2.03
2.5	49	2.54
3.0	34	3.04



W system	lm system	optics	code
12W	427	15°	M2235L12W-30N15-B
12W	582	30°	M2235L12W-30N30-B
12W	734	40°	M2235L12W-30N40-B
12W	703	55°	M2235L12W-30N55-B