

CUPOLA ZOOM



Φ75 Adjustable Round




cutout :75mm




Adjustable Optic



360° Movability




Choose your light



10°-45°


ZOOM

- IP Rating:** IP20 and IP44 options
- Optics:** 10°-45°
- UGR:** < 10
- CRI:** 92Ra with 98Ra option
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K/5000K
- Typical Source**
- Efficacy (lm/W):** 133
- Control:** On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
- Binning** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 36V 150mA 6W
DC 36V 200mA 8W
DC 36V 250mA 10W
DC 36V 300mA 12W
- Ambient temp:** -20 °C to 45 °C
- Class:** II



10W Ra92 3000K 15°

h(m)	E(lx)	D(m)
0.5	6134	0.14
1.0	1533	0.28
1.5	682	0.42
2.0	383	0.56
2.5	245	0.70
3.0	170	0.84



10W Ra92 3000K 45°

h(m)	E(lx)	D(m)
0.5	793	0.50
1.0	198	1.00
1.5	88	1.50
2.0	50	2.00
2.5	32	2.50
3.0	22	3.00



DuraGreen project:
SOK Steak house



W system	lm system	optics	code
6W	520	10°- 45°	AFZ7506W-30N1045-W



W system	lm system	optics	code
8W	668	10°- 45°	AFZ7508W-30N1045-W



W system	lm system	optics	code
10W	970	10°- 45°	AFZ7510W-30N1045-W



W system	lm system	optics	code
12W	1029	10°- 45°	AFZ7512W-30N1045-W