


# DIVINO

## Φ35 Recessed Adjustable Spotlight




Adjustable Optic




 Black Painted




Recessed Trim



Recessed Trimless




- IP Rating:** IP20 and IP44 options
- Optics:** 15°/30°/40°/55°
- UGR:** <10
- CRI:** 98Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K
- Typical Source**
- Efficacy (lm/W):** 110
- Control:** On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
- Binning:** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 36V 300mA 12W
- Ambient temp:** -20 °C to 45 °C
- Class:** II
- Optional accessories:** Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter




12W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	7106	0.14
1.0	1777	0.27
1.5	790	0.41
2.0	444	0.55
2.5	284	0.68
3.0	197	0.82




12W Ra98 3000K 30°

h(m)	E(lx)	D(m)
0.5	3379	0.28
1.0	845	0.56
1.5	375	0.84
2.0	211	1.12
2.5	135	1.40
3.0	94	1.68



12W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	2710	0.38
1.0	678	0.75
1.5	301	1.13
2.0	169	1.50
2.5	108	1.88
3.0	75	2.26



12W Ra98 3000K 55°

h(m)	E(lx)	D(m)
0.5	1235	0.51
1.0	309	1.01
1.5	137	1.52
2.0	77	2.03
2.5	49	2.54
3.0	34	3.04



<b>W system</b>	<b>lm system</b>	<b>optics</b>	<b>code</b>
12W	427	15°	MAR35L12W-30N15-B
12W	582	30°	MAR35L12W-30N30-B
12W	734	40°	MAR35L12W-30N40-B
12W	703	55°	MAR35L12W-30N55-B



<b>W system</b>	<b>lm system</b>	<b>optics</b>	<b>code</b>
12W	427	15°	MAT35L12W-30N15-B
12W	582	30°	MAT35L12W-30N30-B
12W	734	40°	MAT35L12W-30N40-B
12W	703	55°	MAT35L12W-30N55-B