

High Efficiency Part L Compliant

L1≥75 Dwellings compliant (light Source lumens per circuit watt)

L2≥95 Commercial Buildings Compliant(average luminaire efficacy per circuit-watt)

Φ57 Engine

Trimless Adjustable Round Downlight


86 Lm/CW



cutout:57mm




Adjustable Optic



baffle




- IP Rating:** IP44 and IP65 options (from the front)
- Optics:** 17°/21°/31°
- UGR:** <10
- CRI(typ)(R9):** 92 (65)
- CCT:** 3000K
- Typical Source**
- Efficacy (lm/W):** 140(Luminus CXM Gen6)
- Binning:** 2 Step MacAdams
- Lifetime:** >50,000 hrs (L70 B10)
- Input:** AC220-240V 50/60Hz
- Input Voltage(typ):** 33V
- Drive Current:** 200mA
- LED Power:** 6.6W
- Power inc. Driver:** 8W
- Control:** On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
- Ambient temp:** -20 °C to 45 °C
- Class:** II
- Optional accessories:** Honeycomb louvre, Spread Filter, Colour Filter
- Material:** Fine aluminium 6063A
- Fire resistance test:** 60 minutes
- Weight (kg):** 0.2




8W 92 (65) 3000K 17°

h(m)	E(lx)	D(m)
0.5	10318	0.15
1.0	2580	0.30
1.5	1146	0.45
2.0	645	0.60
2.5	413	0.75
3.0	287	0.90



8W 92 (65) 3000K 21°

h(m)	E(lx)	D(m)
0.5	8062	0.19
1.0	2015	0.38
1.5	896	0.57
2.0	504	0.76
2.5	322	0.94
3.0	224	1.13



8W 92 (65) 3000K 31°

h(m)	E(lx)	D(m)
0.5	4538	0.28
1.0	1135	0.57
1.5	504	0.85
2.0	284	1.13
2.5	182	1.41
3.0	126	1.70



W system	CCT	lm system	Luminaire		
			Lm/CW	optics	code
8W	3000K	685	85	17°	AFL5708W-TL-H30N17-W
8W	3000K	695	86	21°	AFL5708W-TL-H30N21-W
8W	3000K	677	84	31°	AFL5708W-TL-H30N31-W