











DRIVERS

DuraGreen supplies a wide range of professional LED drivers under the DuraGreen brand, as well as the most famous international LED driver brands for any type of lighting project. The options are limitless, all with a 5-year warranty.



150mA 36V LED Driver	 click here for spec	 click here for spec	 click here for spec	 click here for spec	 click here for spec	 click here for spec	 click here for spec	 click here for spec	 click here for spec	 click here for spec
	XGL007C0250 SLEW-A7-12	SE-12-100-400 -GIT	SE-12-100-400 -W1A	SE-12-100-400 -W1DS	SE-12-100-450 -W2D	GC2896	GC6888-0/1-10V	GC6888-DALI	SRP-ZG9105N -15CCT100-700	OT Wi 18/220-240 /1A0 NFC CA LP I
Brand	DuraGreen	Ltech	Ltech	Ltech	Ltech	DuraGreen	DuraGreen	DuraGreen	DuraGreen	Osram
Dimmable	no	Triac	0/1-10V	DALI DT6	DALI DT8	Triac	0/1-10V	DALI DT6	Zigbee 2CH	Casambi
Output Current (mA)	150mA	150mA	150mA	150mA	150mA	150mA	150mA	150mA	150mA	150mA
Output Voltage (V)	25-40V	9-42V	9-42V	9-42V	9-42V	9-42V	9-42V	9-42V	6-42V	10-54V
LED Power (W)	5.4W	5.4W	5.4W	5.4W	5.4W	5.4W	5.4W	5.4W	5.4W	5.4W
System Power	6W	7W	7W	7W	7W	7W	7W	7W	7W	7W
Dimensions L x W x H (mm)	80x40x22	111x35x20	135x30x20	135x30x20	111x35x20	128x29x20	128x29x20	128x29x20	135x35x20	150x43x22

note: recommend using 150mA for dimmable products rated at 8W, such as MF45, AFL45, AFL50