DRIVERS

DuraGreen supplies a wide range of professional LED drivers under the DuraGreen brand, as well as the most famous international LED driver brands for any type of lighting project. The options are limitless, all with a 5-year warranty.



200mA 36V LED Driver	click here for spec XGL007C0250 SLEW-A7-12	click here for spec SE-12-100-400 -G1T	click here for spec SE-12-100-400 -W1A	click here for spec SE-12-100-400 -W1DS	click here for spec SE-12-100-450 -W2D	click here for spec	click here for spec GC6888-0/1-10V	click here for spec	click here for spec SRP-ZG9105N -15CCT100-700	click here for spec OT Wi 18/220-240 /1A0 NFC CA LP I
Brand	DuraGreen	Ltech	Ltech	Ltech	Ltech	DuraGreen	DuraGreen	DuraGreen	DuraGreen	Osram
Dimmable	no	Triac	0/1-10V	DALI DT6	DALI DT8	Triac	0/1-10V	DALI DT6	Zigbee 2CH	Casambi
Output Current (mA)	200mA	200mA	200mA	200mA	200mA	200mA	200mA	200mA	200mA	200mA
Output Voltage (V)	25-40V	9-42V	9-42V	9-42V	9-42V	9-42V	9-42V	9-42V	6-42V	10-54V
LED Power (W)	7.2W	7.2W	7.2W	7.2W	7.2W	7.2W	7.2W	7.2W	7.2W	7.2W
System Power	8W	9W	9W	9W	9W	9W	9W	9W	9W	9W
Dimensions L x W x H (mm)	80x40x22	111x35x2O	135x30x20	135x30x20	111x35x2O	128×29×20	128×29×20	128×29×20	135×35×20	150×43×22

note: recommend using 200mA for dimmable products rated at 10W, such as MF55, AFL55, AFL60, and AFL57

DRIVERS

DuraGreen supplies a wide range of professional LED drivers under the DuraGreen brand, as well as the most famous international LED driver brands for any type of lighting project. The options are limitless, all with a 5-year warranty.



250mA 36V LED Driver	click here for spec XGL007C0250 SLEW-A7-12	click here for spec SE-12-100-400 -G1T	click here for spec SE-12-100-400 -W1A	click here for spec SE-12-100-400 -W1DS	click here for spec SE-12-100-450 -W2D	click here for spec	click here for spec GC6888-0/1-10V	click here for spec	click here for spec SRP-ZG9105N -15CCT100-700	click here for spec OT Wi 18/220-240 /1AO NFC CA LP I
Brand	DuraGreen	Ltech	Ltech	Ltech	Ltech	DuraGreen	DuraGreen	DuraGreen	DuraGreen	Osram
Dimmable	no	Triac	0/1-10V	DALI DT6	DALI DT8	Triac	0/1-10V	DALI DT6	Zigbee 2CH	Casambi
Output Current (mA)	250mA	250mA	250mA	250mA	250mA	250mA	250mA	250mA	250mA	250mA
Output Voltage (V)	25-40V	9-42V	9-42V	9-42V	9-42V	9-42V	9-42V	9-42V	6-42V	10-54V
LED Power (W)	9W	9W	9W	9W	9W	9W	9W	9W	9W	9W
System Power	10W	11W	11W	11W	11W	11W	11W	ııW	11W	11W
Dimensions L x W x H (mm)	80x40x22	111x35x2O	135x3Ox2O	135x3Ox2O	111x35x2O	128×29×20	128×29×20	128×29×20	135×35×20	150×43×22

note: recommend using 200mA for dimmable products rated at 10W, such as MF55, AFL55, AFL60, and AFL57

DRIVERS

DuraGreen supplies a wide range of professional LED drivers under the DuraGreen brand, as well as the most famous international LED driver brands for any type of lighting project. The options are limitless, all with a 5-year warranty.



300mA 36V LED Driver	click here for spec XGL015C0350 SLEW-A7-12	click here for spec SE-12-100-400 -G1T	click here for spec SE-12-100-400 -W1A	click here for spec SE-12-100-400 -W1DS	click here for spec SE-12-100-450 -W2D	click here for spec	click here for spec	click here for spec	click here for spec SRP-ZG9105N -15CCT100-700	click here for spec OT Wi 18/220-240 /1AO NFC CA LP I
Brand	DuraGreen	Ltech	Ltech	Ltech	Ltech	DuraGreen	DuraGreen	DuraGreen	DuraGreen	Osram
Dimmable	no	Triac	0/1-10V	DALI DT6	DALI DT8	Triac	0/1-10V	DALI DT6	Zigbee 2CH	Casambi
Output Current (mA)	300mA	300mA	300mA	300mA	300mA	300mA	300mA	300mA	300mA	300mA
Output Voltage (V)	25-40V	9-42V	9-42V	9-42V	9-42V	9-42V	9-42V	9-42V	6-42V	10-54V
LED Power (W)	10.8W	10.8W	10.8W	10.8W	10.8W	10.8W	10.8W	10.8W	10.8W	10.8W
System Power	12W	13W	13W	13W	13W	13W	13W	13W	13W	13W
Dimensions L x W x H (mm)	80x40x22	111x35x2O	135x30x20	135x30x20	111x35x2O	128×29×20	128×29×20	128×29×20	135×35×20	150×43×22