

CUPOLA

Φ114 Bowl Pendant



Fixed Optic



Ceiling hook to move light point



White Painted



Black Painted



Recessed Trim



cutout :58mm

Ø62.5

17.5

1200

Ø114



Surface


Ø50

84


1200

Ø114

IP Rating:	IP20
Optics:	10°/24°/36°/55°
UGR:	< 10
CRI:	98Ra
Lifetime:	> 50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K/2000K-3000K/1800K-4000K/2700K-6500K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W
Ambient temp:	-20 C to 45 C
Class:	II



W system	lm system	optics	code
6W	376	10°	PURSE11406W-30N10-W
6W	597	24°	PURSE11406W-30N24-W
6W	590	36°	PURSE11406W-30N36-W
6W	545	55°	PURSE11406W-30N55-W



W system	lm system	optics	code
8W	445	10°	PURSE11408W-30N10-W
8W	738	24°	PURSE11408W-30N24-W
8W	736	36°	PURSE11408W-30N36-W
8W	672	55°	PURSE11408W-30N55-W



W system	lm system	optics	code
6W	376	10°	PUSSE11406W-30N10-B
6W	597	24°	PUSSE11406W-30N24-B
6W	590	36°	PUSSE11406W-30N36-B
6W	545	55°	PUSSE11406W-30N55-B



W system	lm system	optics	code
8W	445	10°	PUSSE11408W-30N10-B
8W	738	24°	PUSSE11408W-30N24-B
8W	736	36°	PUSSE11408W-30N36-B
8W	672	55°	PUSSE11408W-30N55-B