

# CUPOLA

## Φ114 Surface Downlight



Fixed



Ø114mm



White Painted



Black Painted

<b>IP Rating:</b>	IP20
<b>Optics:</b>	10°/24°/36°/55°
<b>UGR:</b>	<10
<b>CRI:</b>	98Ra
<b>Lifetime:</b>	>50,000 hrs (L70 B10)
<b>CCT:</b>	2700K/3000K
<b>Typical Source</b>	
<b>Efficacy (lm/W):</b>	110
<b>Control:</b>	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
<b>Binning</b>	2 Step MacAdams
<b>Input:</b>	AC220-240V 50/60Hz
<b>Output:</b>	DC 36V 150mA 6W DC 36V 200mA 8W
<b>Ambient temp:</b>	-20 C to 45 C
<b>Class:</b>	II



W system	lm system	optics	code
6W	376	10°	CUSSE11406W-30N10-W
6W	597	24°	CUSSE11406W-30N24-W
6W	590	36°	CUSSE11406W-30N36-W
6W	545	55°	CUSSE11406W-30N55-W



W system	lm system	optics	code
8W	445	10°	CUSSE11408W-30N10-W
8W	738	24°	CUSSE11408W-30N24-W
8W	736	36°	CUSSE11408W-30N36-W
8W	672	55°	CUSSE11408W-30N55-W