



CUPOLA 48V

Φ114

48V Surface Downlight



minimal track



standard track



White Painted



Black Painted

IP Rating:	IP20
Optics:	10°/24°/36°/55°
UGR:	< 10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K/2700K-6000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	48 VDC
Output:	DC 36V 150mA 6W DC 36V 200mA 8W
Ambient temp:	-20 C to 45 C
Class:	III



W system	lm system	optics	code
6W	376	10°	M22CUSSE11406W-30N10-B
6W	597	24°	M22CUSSE11406W-30N24-B
6W	590	36°	M22CUSSE11406W-30N36-B
6W	545	55°	M22CUSSE11406W-30N55-B



W system	lm system	optics	code
8W	445	10°	M22CUSSE11408W-30N10-B
8W	738	24°	M22CUSSE11408W-30N24-B
8W	736	36°	M22CUSSE11408W-30N36-B
8W	672	55°	M22CUSSE11408W-30N55-B