

# ACME SQUARE

## Φ68 Engine


### Adjustable Square Downlight



cutout :80\*80mm



Adjustable Optic



bezel | baffle



White Painted 9016




Black Painted 9005

<b>IP Rating:</b>	IP20 and IP44 options
<b>Optics:</b>	15°/24°/36°/50°
<b>UGR:</b>	<10
<b>CRI:</b>	98Ra
<b>Lifetime:</b>	>50,000 hrs (L70 B10)
<b>CCT:</b>	2700K/3000K/3500K/4000K/5000K/ 2000K-3000K/1800K-4000K/2700K-6000K

<b>Typical Source</b>	
<b>Efficacy (lm/W):</b>	110
<b>Control:</b>	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
<b>Binning</b>	2 Step MacAdams
<b>Input:</b>	AC220-240V 50/60Hz
<b>Output:</b>	DC 36V 200mA 8W DC 36V 250mA 10W DC 36V 300mA 12W


<b>Ambient temp:</b>	-20 °C to 45 °C
<b>Class:</b>	II
<b>Optional accessories:</b>	Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter

<b>Ceiling Thickness:</b>	9mm-28mm
<b>Material:</b>	Fine aluminium 6063A
<b>Fire resistance test:</b>	60 minutes




12W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	10897	0.17
1.0	2724	0.33
1.5	1211	0.50
2.0	681	0.66
2.5	436	0.83
3.0	303	0.99




12W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	5992	0.22
1.0	1498	0.45
1.5	666	0.67
2.0	375	0.89
2.5	240	1.12
3.0	166	1.34




12W Ra98 3000K 36°


h(m)	E(lx)	D(m)
0.5	3401	0.31
1.0	850	0.62
1.5	378	0.93
2.0	213	1.25
2.5	136	1.56
3.0	94	1.87



<b>W system</b>	<b>lm system</b>	<b>optics</b>	<b>code</b>
8W	487	15°	AFL6808W-Q-30N15-B
8W	503	24°	AFL6808W-Q-30N24-B
8W	492	36°	AFL6808W-Q-30N36-B
8W	427	50°	AFL6808W-Q-30N50-B



<b>W system</b>	<b>lm system</b>	<b>optics</b>	<b>code</b>
10W	553	15°	AFL6810W-Q-30N15-B
10W	575	24°	AFL6810W-Q-30N24-B
10W	565	36°	AFL6810W-Q-30N36-B
10W	485	50°	AFL6810W-Q-30N50-B



<b>W system</b>	<b>lm system</b>	<b>optics</b>	<b>code</b>
12W	635	15°	AFL6812W-Q-30N15-B
12W	773	24°	AFL6812W-Q-30N24-B
12W	763	36°	AFL6812W-Q-30N36-B
12W	655	50°	AFL6812W-Q-30N50-B

ACME



Black Nickel

---



Solid Brass



Antique Bronze

---



Black Painted 9005



White Painted 9016

---



Brushed Grey



Polished Chrome

Our light fixtures are made of the highest quality metal materials, like pure aluminium and solid brass. Our process is precise and sustainable to achieve circular products that last longer and look stylish.

The ACME light engines come in three distinct shapes: straight baffle for maximum brightness, curve baffle for a softer light effect, and semi-recessed baffle for added ceiling decoration. They are available in five different sizes with both trimmed and trimless bezels (cutouts of 50mm, 57mm, 68mm, and 78mm) and offered in seven standard finishes including white 9016, black 9005, polished chrome, black nickel, antique bronze, and solid brass.



ACME STRAIGHT



ACME CURVE



ACME SEMI

We transform premium materials into fine luxury goods that elevate any space.



Light engine



Installation frame trimless



Installation frame trim

Circular economy principles are intricately woven into every stage of our design and manufacturing process, making ACME downlights a shining example of sustainability. These fixtures are fully modular, allowing for easy repair, reuse, and end-of-life reintroduction into standard stock.

Safety wire



Accessories

Spread



Double Asymmetric



Honeycomb



Red filter



Blue filter



Amber filter



