


Φ68 Engine Wall Light




Fixed Optic



-  White Painted
-  Black Painted
-  Antique Bronze
-  Brushed Grey


- IP Rating:** IP20 and IP44 options
- Optics:** 15°/24°/36°/50°
- UGR:** <10
- CRI:** 98Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K/5000K/
2000K-3000K/1800K-4000K/2700K-6000K

- Typical Source Efficacy (lm/W):** 110
- Control:** On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
- Binning:** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 36V 200mA 8Wx2
DC 36V 250mA 10Wx2
DC 36V 300mA 12Wx2
- Ambient temp:** -20 °C to 45 °C
- Class:** II
- Optional accessories:** Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter
- Material:** Fine aluminium 6063A




h(m)	E(lx)	D(m)
0.5	10897	0.17
1.0	2724	0.33
1.5	1211	0.50
2.0	681	0.66
2.5	436	0.83
3.0	303	0.99

12W Ra98 3000K 15°




h(m)	E(lx)	D(m)
0.5	8621	0.20
1.0	2155	0.41
1.5	958	0.61
2.0	539	0.81
2.5	345	1.02
3.0	239	1.22

12W Ra98 3000K 24°



h(m)	E(lx)	D(m)
0.5	4792	0.28
1.0	1198	0.55
1.5	532	0.83
2.0	300	1.10
2.5	192	1.38
3.0	133	1.65

12W Ra98 3000K 36°



h(m)	E(lx)	D(m)
0.5	1608	0.47
1.0	402	0.93
1.5	179	1.40
2.0	100	1.87
2.5	64	2.33
3.0	45	2.80

12W Ra98 3000K 50°



W system	Im system	optics	code
8Wx2	487x2	15°	WQE6808Wx2-30N15-B
8Wx2	503x2	24°	WQE6808Wx2-30N24-B
8Wx2	492x2	36°	WQE6808Wx2-30N36-B
8Wx2	427x2	50°	WQE6808Wx2-30N50-B



W system	Im system	optics	code
10Wx2	553x2	15°	WQE6810Wx2-30N15-B
10Wx2	575x2	24°	WQE6810Wx2-30N24-B
10Wx2	565x2	36°	WQE6810Wx2-30N36-B
10Wx2	485x2	50°	WQE6810Wx2-30N50-B



W system	Im system	optics	code
12Wx2	717x2	15°	WQE6812Wx2-30N15-B
12Wx2	760x2	24°	WQE6812Wx2-30N24-B
12Wx2	750x2	36°	WQE6812Wx2-30N36-B
12Wx2	640x2	50°	WQE6812Wx2-30N50-B

ACME



Black Nickel



Solid Brass



Antique Bronze



Black Painted 9005



White Painted 9016



Brushed Grey



Polished Chrome

Our light fixtures are made of the highest quality metal materials, like pure aluminium and solid brass. Our process is precise and sustainable to achieve circular products that last longer and look stylish.

The ACME light engines come in three distinct shapes: straight baffle for maximum brightness, curve baffle for a softer light effect, and semi-recessed baffle for added ceiling decoration. They are available in five different sizes with both trimmed and trimless bezels (cutouts of 50mm, 57mm, 68mm, and 78mm) and offered in seven standard finishes including white 9016, black 9005, polished chrome, black nickel, antique bronze, and solid brass.



ACME STRAIGHT



ACME CURVE



ACME SEMI

We transform premium materials into fine luxury goods that elevate any space.



Light engine



Installation frame trimless



Installation frame trim

Circular economy principles are intricately woven into every stage of our design and manufacturing process, making ACME downlights a shining example of sustainability. These fixtures are fully modular, allowing for easy repair, reuse, and end-of-life reintroduction into standard stock.

Safety wire



Accessories

Spread



Double Asymmetric



Honeycomb



Red filter



Blue filter



Amber filter



