

MOOD STAR


Φ35 Adjustable Round




cutout:35mm



Adjustable Optic




True non-intrusive-in lighting solutions to integrate lighting with architecture



3W Ra92 3000K 15°

h(m)	E(lx)	D(m)
0.5	4168	0.11
1.0	1042	0.23
1.5	463	0.34
2.0	261	0.46
2.5	167	0.57
3.0	116	0.65



3W Ra92 3000K 30°

h(m)	E(lx)	D(m)
0.5	855	0.25
1.0	214	0.50
1.5	95	0.75
2.0	53	1.00
2.5	34	1.26
3.0	24	1.51

IP Rating:	IP20
Optics:	15°/30°
UGR:	<17
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K
Typical Source Efficacy (lm/W):	103
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 3V 300mA 1.3W DC 3V 650mA 3W
Ambient temp:	-20 °C to 45 °C
Class:	II



W system	lm system	optics	code
1.3W	68	15°	AFL351.3W-30NL15-W
1.3W	85	30°	AFL351.3W-30NL30-W



W system	lm system	optics	code
3W	148	15°	AFL3503W-30NL15-W
3W	179	30°	AFL3503W-30NL30-W