

ACME SPY

Φ57 In/out Spotlights



cutout: 57mm



Adjustable Optic




matt white painted




matt black painted



Recessed Trim




Recessed Trimless



IP Rating:	IP20 and IP44 options
Optics:	15°/24°/36°
UGR:	< 10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K/ 2000K-3000K/1800K-4000K/2700K-6000K


Typical Source

Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 200mA 8W
Ambient temp:	-20 °C to 45 °C
Class:	II
Material:	Fine aluminium 6063A




8W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	7550	0.11
1.0	1888	0.22
1.5	839	0.34
2.0	472	0.45
2.5	302	0.56
3.0	210	0.67



8W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	2868	0.24
1.0	717	0.49
1.5	319	0.73
2.0	179	0.98
2.5	115	1.22
3.0	80	1.46



8W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	2108	0.36
1.0	527	0.72
1.5	234	1.08
2.0	132	1.44
2.5	84	1.80
3.0	59	2.16



DuraGreen project:
CO | Michelin Stared Restaurant



W system	lm system	optics	code
8W	328	15°	AFL5708W-IO-30N15-B
8W	404	24°	AFL5708W-IO-30N24-B
8W	499	36°	AFL5708W-IO-30N36-B



W system	lm system	optics	code
8W	328	15°	AFL5708W-IO-TL-30N15-B
8W	404	24°	AFL5708W-IO-TL-30N24-B
8W	499	36°	AFL5708W-IO-TL-30N36-B

Designed with ease and convenience in mind, these fixtures feature a user-friendly pull mechanism that enables your favorite pieces, artwork, or decor to be highlighted. From sculptures to paintings, let ACME SPY bring your treasures to life with precise, targeted radiance, adding both function and form to your stylish space.



DuraGreen project:
AXENT Showroom