



ORBIT 48V

Φ65 Adjustable 48V Track Light




IP Rating:	IP20
Optics:	12°/20°/36°/50°
UGR:	< 10
CRI:	98Ra
Lifetime:	> 50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/5000K/ 2000K-3000K/1800K-4000K/2700K-6000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	48 VDC
Output:	DC 36V 700mA 30W
Ambient temp:	-20 C to 45 C
Class:	III
Optional accessories:	Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter



30W Ra98 3000K 20°

h(m)	E(lx)	D(m)
1.0	7321	0.36
2.0	1830	0.71
3.0	813	1.10
4.0	450	1.40
5.0	293	1.80
6.0	203	2.10



30W Ra98 3000K 36°

h(m)	E(lx)	D(m)
1.0	2993	0.83
2.0	748	1.30
3.0	333	0.90
4.0	187	2.50
5.0	120	3.20
6.0	83	3.80



DuraGreen project:
Poltrona Frau Flagship Store



W system	lm system	optics	code
30W	1706	15°	M226530W-30N15-B
30W	2219	24°	M226530W-30N24-B
30W	2184	36°	M226530W-30N36-B
30W	1965	50°	M226530W-30N50-B