


ARTFOCUS 48V

Φ36


Adjustable 48V Track Light



Adjustable Optic



minimal track



standard track




matt white painted




matt black painted

- IP Rating:** IP20 and IP44 options
- Optics:** 15°/28°/36°
- UGR:** <10
- CRI:** 98Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K/5000K/
2000K-3000K/1800K-4000K/2700K-6000K
- Typical Source Efficacy (lm/W):** 110
- Control:** On/off, 0/1-10V, Dali, Zigbee, Casambi
- Binning:** 2 Step MacAdams
- Input :** 48 VDC
- Output :** DC 36V 150mA 6W
- Ambient temp:** -20 °C to 45 °C
- Class:** III
- Material:** structure fine aluminum 6063A




6W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	4937	0.14
1.0	1234	0.27
1.5	549	0.41
2.0	309	0.54
2.5	197	0.68
3.0	137	0.81



6W Ra98 3000K 28°

h(m)	E(lx)	D(m)
0.5	2848	0.25
1.0	712	0.49
1.5	316	0.74
2.0	178	0.98
2.5	114	1.23
3.0	79	1.47



6W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	1706	0.31
1.0	426	0.62
1.5	190	0.93
2.0	107	1.25
2.5	68	1.56
3.0	47	1.87



DuraGreen project:
Steve O Art



W system	lm system	optics	code
6W	373	15°	TK3606W-30N15-B
6W	445	28°	TK3606W-30N28-B
6W	446	36°	TK3606W-30N36-B