

SYSTEM 68

Φ68 GLAMO


Universal Tunable White Track Light Knob Dim 3 phase 4 wire



Adjustable Optic



Zoom 15°-50°



Knob Dim



CCT



matt white painted




matt black painted



Bespoke



Spot 5°/10°/15°/24°/36°/50°



IP Rating:

IP20 and IP44 options

Optics:

5°/10°/15°/24°/36°/50°/Zoomable 15°-50°

UGR:

<17

CRI:

98Ra

Lifetime:

>50,000 hrs (L70 B10)

CCT:

2700K-6000K

Typical Source

Efficacy (lm/W):

110

Control:

on-board dim, CCT bar (WW,NW,CW)

Binning:

2 Step MacAdams

Input:

AC220-240V 50/60Hz

Output:

DC 36V 300mA 12W

Ambient temp:

-20 °C to 45 °C

Class:

II

Optional Accessories


(fixed beam):

Honeycomb Louvre, Linear Filter

Phase Track Brand:


NORLUX / NORDIC / POWERGEAR / GLOBAL / NUCO / EUTRAC / STAFF / ERCO / ONETRACK
SG SHOPLINE / NL POWER / HOFFMEISTER / CONCORD / UNIPRO / ZUMTOBEL

Spot




12W Ra98 3000K 5°

h(m)	E(lx)	D(m)
0.5	34822	0.05
1.0	8706	0.10
1.5	3869	0.16
2.0	2176	0.21
2.5	1393	0.26
3.0	967	0.31




12W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	8729	0.22
1.0	2182	0.44
1.5	970	0.67
2.0	546	0.89
2.5	349	1.11
3.0	242	1.33




12W Ra98 3000K 10°

h(m)	E(lx)	D(m)
0.5	31107	0.08
1.0	7777	0.16
1.5	3456	0.24
2.0	1944	0.32
2.5	1244	0.40
3.0	864	0.48




12W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	4056	0.32
1.0	1014	0.65
1.5	451	0.97
2.0	253	1.29
2.5	162	1.61
3.0	113	1.94



12W Ra98 3000K 15°


h(m)	E(lx)	D(m)
0.5	27091	0.12
1.0	6773	0.24
1.5	3010	0.36
2.0	1693	0.48
2.5	1084	0.60
3.0	753	0.72



12W Ra98 3000K 50°


h(m)	E(lx)	D(m)
0.5	1661	0.44
1.0	415	0.89
1.5	185	1.33
2.0	104	1.77
2.5	66	2.22
3.0	46	2.66

Zoom




12W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	12099	0.14
1.0	3025	0.27
1.5	1344	0.41
2.0	756	0.54
2.5	484	0.68
3.0	336	0.81




12W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	2174	0.38
1.0	544	0.76
1.5	242	1.14
2.0	136	1.52
2.5	87	1.90
3.0	60	2.28



Spot

W system	lm system	optics	code
12W	316	5°	TK6812W-2760N05
12W	710	10°	TK6812W-2760N10
12W	1014	15°	TK6812W-2760N15
12W	985	24°	TK6812W-2760N24
12W	950	36°	TK6812W-2760N36
12W	1005	50°	TK6812W-2760N50



Zoom

W system	lm system	optics	code
12W	756-747	15° -50°	TK6812W-2760N1550