




NEONFLEX

NEON STRIP 1010 BEND SIDE

flexible on the vertical axis




BEND SIDE




AP1010U



Accessories not included



Clips (AC1010U)



Rigid Profile (AP1010U)



Flexible Profile (AF1010U)

IP Rating:	IP67
Optics:	115°
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/4000K/6500K
Typical Source Efficacy (lm/W):	113
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning:	2 Step MacAdams
Voltage:	DC 24V
Power(W):	7W/m , 10W/m
Ambient temp:	-20 °C to 45 °C
Class:	III



W system	lm system	optics	code
7W	50Lm /W	115°	E67-BS1010-07W-27
7W	50Lm /W	115°	E67-BS1010-07W-30
7W	52Lm /W	115°	E67-BS1010-07W-40
7W	52Lm /W	115°	E67-BS1010-07W-65



W system	lm system	optics	code
10W	50Lm /W	115°	E67-BS1010-10W-27
10W	50Lm /W	115°	E67-BS1010-10W-30
10W	52Lm /W	115°	E67-BS1010-10W-40
10W	52Lm /W	115°	E67-BS1010-10W-65