


# BELLA PRO

## Spotlight- Adjustable - Optic Wide 3000K



Adjustable Optic



SKU : EN-RT4106W-30N40

### Main specifications

<b>LED Module Power:</b>	150mA 5.4W
<b>System Power(inc. driver):</b>	150mA 6.5W
<b>Typical Source Efficacy (lm/W):</b>	110
<b>Delivered Lumens (lm):</b>	558
<b>Delivered Lumens Per Circuit Watt:</b>	86

### Photometric

<b>Beam Angle:</b>	Wide 40°
<b>CCT:</b>	3000K
<b>CRI:</b>	98Ra
<b>Binning:</b>	2 Step MacAdams
<b>Lifetime:</b>	L80 B50 50,000hrs @25°C Ta
<b>UGR:</b>	<10

### Electrical


<b>Insulation Class:</b>	III
<b>Forward Voltage :</b>	36V
<b>LED Current:</b>	150mA
<b>Power Supply:</b>	Remote excluded
<b>Dimmable:</b>	Yes
<b>Control:</b>	DALI

### Physical

<b>IP Rating:</b>	IP20 Front
<b>Optional Accessories:</b>	Honeycomb / Spread Filter
<b>Material:</b>	Fine aluminum 6063A

### Certifications

CB/CE/UKCA/GLOBAL MARK



h(m)	E lx	D(m)
0.5	2309	0.39
1.0	577	0.77
1.5	257	1.16
2.0	144	1.54
2.5	92	1.93
3.0	64	2.32


6W Ra98 3000K 40°

# Accessories

## Bezels


---

### Trimless



SKU : BZ-36-TL

### Mini-Trim



Black Painted  
9005

SKU : BZ-40-BK

White Painted  
9016

SKU : BZ-40-WH

## Lenses

---



### Narrow

SKU : LS-25-NR



### Medium

SKU : LS-25-MD



### Wide

SKU : LS-25-WD



### Super Wide

SKU : LS-25-SW

## Filters

---



Honeycomb  
SKU : HB-25



Spread  
SKU : SP-25

## Power Supply

---

Constant current power supply, dimmable DALI 2

SKU : LC 15/100-400/42 DA SR SNC4

220/240V - 50/60Hz with power current selected through adjustable switch.

Reference for system power - 150mA - 6W



## Assembled Spotlights



Trimless Adjustable Spotlight



Mini-Trim Adjustable Spotlight