


BELLA PRO 48V

Spotlight - Adjustable - Optic Wide 3000K



Adjustable Optic



SKU : MT4106W-30N30

Main specifications

LED Module Power:	150mA 5.4W
System Power(inc. driver):	150mA 6.5W
Typical Source Efficacy (lm/W):	110
Delivered Lumens (lm):	558
Delivered Lumens Per Circuit Watt:	86

Photometric

Beam Angle:	Wide 40°
CCT:	3000K
CRI:	98Ra
Binning:	2 Step MacAdams
Lifetime:	L80 B50 50,000hrs @25°C Ta
UGR:	<10

Electrical


Insulation Class:	III
Forward Voltage :	36V
LED Current:	150mA
Power Supply:	In-built
Dimmable:	Yes
Control:	DALI

Physical

IP Rating:	IP20 Front
Optional Accessories:	Honeycomb / Spread Filter
Material:	Fine aluminum 6063A

Certifications

CB/CE/UKCA/GLOBAL MARK



6W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	2309	0.39
1.0	577	0.77
1.5	257	1.16
2.0	144	1.54
2.5	92	1.93
3.0	64	2.32

Accessories

Lenses



Narrow

SKU : LS-25-NR



Medium

SKU : LS-25-MD



Wide

SKU : LS-25-WD



Super Wide

SKU : LS-25-SW

Filters



Honeycomb

SKU : HB-25



Spread

SKU : SP-25

Power Supply

Constant voltage power supply, dimmable DALI 2
SKU:MT-100-400-D1D1

48V - 50/60Hz with power current selected through adjustable switch
Reference for system power - 150mA - 6W

