


GLAMO PRO

Spotlight - Adjustable - Optic Wide 3000K



Adjustable Optic



SKU : EN-RT6812W-30N36

Main specifications

LED Module Power:	300mA 10.8W
System Power(inc. driver):	300mA 13W
Typical Source Efficacy (lm/W):	110
Delivered Lumens (lm):	950
Delivered Lumens Per Circuit Watt:	73

Photometric

Beam Angle:	Wide 36°
CCT:	3000K
CRI:	98Ra
Binning:	2
Lifetime:	L80 B50 50,000hrs @25°C Ta
UGR:	<10

Electrical


Insulation Class:	III
Forward Voltage :	36V
LED Current:	300mA
Power Supply:	Remote excluded
Dimmable:	Yes
Control:	DALI

Physical

IP Rating:	IP20 Front
Optional Accessories:	Honeycomb / Spread Filter
Material:	Fine aluminum 6063A

Certifications

CB/CE/UKCA/GLOBAL MARK



13W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	4056	0.32
1.0	1014	0.65
1.5	451	0.97
2.0	253	1.29
2.5	162	1.61
3.0	113	1.94


Accessories

Bezels

Trimless




SKU : BZ-68-TL



Mini-Trim



-  SKU : BZ-68-BK
Black Painted
9005
-  SKU : BZ-68-WH
White Painted
9016



Lenses



Narrow
SKU : LS-50-NR



Medium
SKU : LS-50-MD



Wide
SKU : LS-50-WD



Super Wide
SKU : LS-50-SW

Filters



Honeycomb
SKU : HB-50



Spread
SKU : SP-50

Power Supply

Constant current power supply, dimmable DALI 2

SKU : LC 15/100-400/42 DA SR SNC4

220/240V - 50/60Hz with power current selected through adjustable switch.

Reference for system power

150mA - 6W / 180mA - 8W / 200mA - 9W / 250mA 11W / 300mA 13W



Assembled Spotlights



Trimless Adjustable Spotlight



Mini-Trim Adjustable Spotlight