


System 78

Round - Adjustable - Optic Wide 3000K



Adjustable Optic



SKU : EN-7810W-30N36

Main specifications

LED Module Power:	250mA 9W
System Power(inc. driver):	250mA 10.8W
Typical Source Efficacy (lm/W):	110
Delivered Lumens (lm):	648
Delivered Lumens Per Circuit Watt:	60

Photometric

Beam Angle:	Wide 36°
CCT:	3000K
CRI:	98Ra
Binning:	2 Step MacAdams
Lifetime:	L80 B50 50,000hrs @25°C Ta
UGR:	<10

Electrical


Insulation Class:	III
Forward Voltage :	36V
LED Current:	250mA
Power Supply:	Remote excluded
Dimmable:	Yes
Control:	DALI

Physical

IP Rating:	IP65 Front
Optional Accessories:	Honeycomb / Spread Filter
Material:	Fine aluminum 6063A

Certifications

60 MINUTES FIRE RESISTANCE (UK) / UKCA (UK) / CB / CE (EU) / CCC (CHINA) / GLOBAL MARK (AUSTRALIA)



10.8W Ra98 3000K 36°
Curve Baffle

h(m)	E(lx)	D(m)
0.5	2863	0.30
1.0	716	0.60
1.5	318	0.90
2.0	179	1.20
2.5	115	1.50
3.0	80	1.80


Accessories

Bezels

Trimless



SKU : BZ-78-TL



Mini-Trim




Black Painted
9005

White Painted
9016

SKU : BZ-78-BK

SKU : BZ-78-WH



Baffles

Curve Baffle



Black Painted
9005

White Painted
9016

SKU : BF-78-C-BK

SKU : BF-78-C-WH

Straight Baffle



Black Painted
9005

White Painted
9016

SKU : BF-78-BK

SKU : BF-78-WH

Lenses



Narrow

SKU : LS-50-NR



Medium

SKU : LS-50-MD



Wide

SKU : LS-50-WD



Super Wide

SKU : LS-50-SW

Accessories

Filters



Honeycomb
SKU : HB-50



Spread
SKU : SP-50

Power Supply

Constant current power supply, dimmable DALI 2
SKU : LC 15/100-400/42 DA SR SNC4

220/240V - 50/60Hz with power current selected through adjustable switch.
Reference for system power - 150mA - 6W / 180mA - 8W / 200mA - 9W / 250mA-11W



Assembled System 78 Downlights



78 Curve Baffle Mini-trim



78 Curve Baffle Trimless



78 Straight Baffle Mini-trim



78 Straight Baffle Trimless