

MOOD DOWNLIGHT


Φ45 Adjustable Round



cutout :45mm



Adjustable Optic



baffle



Black Matt



White Matt



Silver Matt



Grey Specular



Black Specular



Silver Specular




Gold Specular




Bespoke

- IP Rating:** IP20 and IP44 options
- Optics:** 15°/24°/36°/50°
- UGR:** <10
- CRI:** 98Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K/5000K/
2000K-3000K/1800K-4000K/2700K-6000K
- Typical Source Efficacy (lm/W):** 110
- Control:** On/off, Mains Dim, 0/1-10V, DALI, Zigbee, Casambi
- Binning:** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 36V 100mA 4W
DC 36V 150mA 6W
DC 36V 200mA 8W
- Ambient temp:** -20 °C to 45 °C
- Class:** II
- Optional accessories:** Honeycomb louvre, Solite Lense, Spread Lense,
Colour Filter




8W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	13964	0.12
1.0	3491	0.24
1.5	1552	0.36
2.0	873	0.48
2.5	559	0.60
3.0	388	0.72




8W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	5171	0.21
1.0	1293	0.43
1.5	575	0.64
2.0	323	0.85
2.5	207	1.06
3.0	144	1.28



8W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	2304	0.31
1.0	576	0.62
1.5	256	0.92
2.0	144	1.23
2.5	92	1.54
3.0	64	1.85



8W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	870	0.44
1.0	218	0.87
1.5	97	1.31
2.0	54	1.75
2.5	35	2.18
3.0	24	2.62



DuraGreen project:
Black Stone Hillside Hotel



W system	lm system	optics	code
4W	295	15°	AFL4504W-30N15-W
4W	333	24°	AFL4504W-30N24-W
4W	322	36°	AFL4504W-30N36-W
4W	330	50°	AFL4504W-30N50-W



W system	lm system	optics	code
6W	425	15°	AFL4506W-30N15-W
6W	464	24°	AFL4506W-30N24-W
6W	455	36°	AFL4506W-30N36-W
6W	465	50°	AFL4506W-30N50-W



W system	lm system	optics	code
8W	495	15°	AFL4508W-30N15-W
8W	562	24°	AFL4508W-30N24-W
8W	552	36°	AFL4508W-30N36-W
8W	562	50°	AFL4508W-30N50-W