

SYSTEM 57


Φ57 ACME Downlight Trimless Adjustable Straight Baffle



cutout :57mm



Adjustable Optic



Standard



Black Painted
9005



White Painted
9016

Curated Finishes (MOQ 20 applies)



Polished Brass



Black Nickel



Bright Chrome



Rose Gold



Solid Brass



Peach Fuzz



Antique Copper



Aged Bronze



Antique Brass



Dark Brass




Brushed Grey



Pearl Nickel


IP Rating:	IP20 and IP44 options
Optics:	15°/24°/36°
UGR:	<10
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K/3500K/4000K/ 1800K-4000K/2700K-6000K
Typical Source Efficacy (lm/W):	140
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W
Ambient temp:	-20 °C to 45 °C
Class:	II
Optional accessories:	Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter
Material:	Fine aluminium 6063A
Fire resistance test:	60 minutes
Certification:	CB/CE/UKCA/GLOBAL MARK/ 60-MINUNTE FIRE RESISTANCE

datasheet - high efficiency 92Ra




10W Ra92 3000K 15°

h(m)	E(lx)	D(m)
0.5	19266	0.12
1.0	4817	0.24
1.5	2141	0.36
2.0	1204	0.48
2.5	771	0.61
3.0	535	0.73




10W Ra92 3000K 24°

h(m)	E(lx)	D(m)
0.5	9887	0.20
1.0	2472	0.41
1.5	1099	0.61
2.0	618	0.81
2.5	395	1.02
3.0	275	1.22




10W Ra92 3000K 36°


h(m)	E(lx)	D(m)
0.5	4269	0.31
1.0	1067	0.63
1.5	474	0.94
2.0	267	1.25
2.5	171	1.57
3.0	119	1.88



W system	lm system(92Ra)	optics	code
6W	560	15°	AFL5706W-TL-H30N15
6W	581	24°	AFL5706W-TL-H30N24
6W	590	36°	AFL5706W-TL-H30N36



W system	lm system(92Ra)	optics	code
8W	725	15°	AFL5708W-TL-H30N15
8W	753	24°	AFL5708W-TL-H30N24
8W	775	36°	AFL5708W-TL-H30N36



W system	lm system(92Ra)	optics	code
10W	858	15°	AFL5710W-TL-H30N15
10W	912	24°	AFL5710W-TL-H30N24
10W	940	36°	AFL5710W-TL-H30N36