

GLAMO

Φ68 Recessed Zoomable 15°-50° Spotlight




Adjustable Optic



-  matt white painted
-  matt black painted




Recessed Trim



Bespoke




Recessed Trimless




- IP Rating:** IP20
- Optics:** Zoomable 15°-50°
- UGR:** <17
- CRI:** 98Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K/5000K/
2000K-3000K/1800K-4000K/2700K-6000K

- Typical Source Efficacy (lm/W):** 110
- Control:** On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
- Binning:** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 36V 300mA 12W
- Ambient temp:** -20 °C to 45 °C
- Class:** II
- Material:** Fine aluminium 6063A



12W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	12099	0.14
1.0	3025	0.27
1.5	1344	0.41
2.0	756	0.54
2.5	484	0.68
3.0	336	0.81



12W Ra98 3000K 40°

h(m)	E(lx)	D(m)
0.5	2174	0.38
1.0	544	0.76
1.5	242	1.14
2.0	136	1.52
2.5	87	1.90
3.0	60	2.28



DuraGreen project:
YELLOWKORNER Art Gallery



Recessed Trim

W system	lm system	optics	code
12W	756-747	15°- 50°	RT6812W-30N1550-B



Recessed Trimless

W system	lm system	optics	code
12W	756-747	15°- 50°	TL6812W-30N1550-B