


ACME 57 48V


Φ57 Adjustable 48V Track Light



Adjustable Optic




minimal track



standard track




- IP Rating:** Front IP44, optional IP65
- Optics:** 15°/24°/36°/50°
- UGR:** < 10
- CRI:** 98Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K
1800-3000K(Warm Dim), 2700K - 6000K (Tunable White)
- Typical Source**
- Efficacy (lm/W):** 110
- Control:** On/off, 0/1-10V, Dali, Zigbee, Casambi
- Binning** 2 Step MacAdams
- Input:** 48 VDC
- Output:** DC 36V 150mA 6W
DC 36V 200mA 8W
DC 36V 250mA 10W
- Ambient temp:** -20 °C to 45 °C
- Class:** III
- Optional accessories:** Honeycomb louvre, Solite Lens, Spread Lens, Colour Filter
- Material:** Fine aluminium 6063A




10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	13172	0.14
1.0	3293	0.28
1.5	1464	0.42
2.0	823	0.56
2.5	527	0.70
3.0	366	0.84




10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	7091	0.21
1.0	1773	0.43
1.5	788	0.64
2.0	443	0.86
2.5	284	1.07
3.0	197	1.29



10W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	3820	0.31
1.0	955	0.63
1.5	424	0.94
2.0	239	1.25
2.5	153	1.57
3.0	106	1.88



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	1678	0.50
1.0	420	1.01
1.5	186	1.51
2.0	105	2.01
2.5	67	2.51
3.0	47	3.02




Pearl Nickel

A silky-smooth pearl sheen with subtle warm gold undertones and refined reflectivity, ideal for contemporary, minimalist, coastal, and transitional luxury homes where it brings clarity and elegant softness to marble, glass, and muted neutrals without feeling cold.



Heritage Brass

A multi-layered, hand-refined deep umber finish with delicate golden undertones and a nuanced patina that embodies Quiet Luxury. Ideal for British classic, organic modern, and bespoke residential interiors, adding a grounded, timeless elegance to marble, dark timber, and artisanal plaster palettes.



W system	lm system	optics	code
6W	450	15°	AFL5706W-MT-30N15
6W	532	24°	AFL5706W-MT-30N24
6W	523	36°	AFL5706W-MT-30N36
6W	464	50°	AFL5706W-MT-30N50



W system	lm system	optics	code
8W	582	15°	AFL5708W-MT-30N15
8W	624	24°	AFL5708W-MT-30N24
8W	661	36°	AFL5708W-MT-30N36
8W	600	50°	AFL5708W-MT-30N50



W system	lm system	optics	code
10W	704	15°	AFL5710W-MT-30N15
10W	751	24°	AFL5710W-MT-30N24
10W	814	36°	AFL5710W-MT-30N36
10W	723	50°	AFL5710W-MT-30N50