

ACME PINHOLE

Φ57 Engine


Trimless Adjustable Downlight



cutout :57mm



Adjustable Optic



baffle




Black Painted
9005




White Painted
9016

- IP Rating:** Front IP44, optional IP65
- Optics:** 15°/24°/36°
- UGR:** <10
- CRI:** 92Ra / 98Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K
1800-3000K(Warm Dim), 2700K - 6000K (Tunable White)
- Typical Source Efficacy (lm/W):** 110
- Control:** On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
- Binning:** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 36V 150mA 6W
DC 36V 200mA 8W
DC 36V 250mA 10W
- Ambient temp:** -20 C to 45 C
- Class:** II
- Optional accessories:** Honeycomb louvre, Solite Lens, Spread Lens, Colour Filter
- Material:** Fine aluminium 6063A
- Certification:** CB/CE/UKCA/GLOBAL MARK/60-MINUNTE FIRE RESISTANCE




10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	12989	0.11
1.0	3247	0.22
1.5	1443	0.34
2.0	812	0.45
2.5	520	0.56
3.0	361	0.67




10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	7428	0.20
1.0	1857	0.40
1.5	825	0.60
2.0	464	0.80
2.5	297	1.00
3.0	206	1.20



10W Ra98 3000K 36°


h(m)	E(lx)	D(m)
0.5	3506	0.29
1.0	877	0.58
1.5	309	0.87
2.0	219	1.15
2.5	140	1.44
3.0	97	1.73



W system	lm system	optics	code
6W	256	15°	AFL5706W-P-TL-30N15
6W	360	24°	AFL5706W-P-TL-30N24
6W	371	36°	AFL5706W-P-TL-30N36



W system	lm system	optics	code
8W	330	15°	AFL5708W-P-TL-30N15
8W	465	24°	AFL5708W-P-TL-30N24
8W	475	36°	AFL5708W-P-TL-30N36



W system	lm system	optics	code
10W	397	15°	AFL5710W-P-TL-30N15
10W	628	24°	AFL5710W-P-TL-30N24
10W	574	36°	AFL5710W-P-TL-30N36