

ACME ALABASTER


Φ68 ACME Downlight /Wall Light Trimless Fixed Alabaster Globe



cutout: 68mm



Fixed Optic




baffle



Alabaster




IP Rating:	Front IP44, optional IP65
Optics:	120°
UGR:	< 10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 200mA 8W DC 36V 250mA 10W DC 36V 300mA 12W
Ambient temp:	-20 °C to 45 °C
Class:	II
Material:	Fine Aluminium 6063A + Alabaster Stone
Fire resistance test:	60 minutes
Certification:	CB/CE/UKCA/GLOBAL MARK/60-MINUNTE FIRE RESISTANCE



12W Ra98 3000K 120°

h(m)	E(x)	D(m)
0.5	59	1.24
1.0	15	2.48
1.5	7	3.72
2.0	4	4.96



W system	lm system	optics	code
8W	235	120°	AFL6808W-AG-TL-30N120
10W	286	120°	AFL6810W-AG-TL-30N120
12W	337	120°	AFL6812W-AG-TL-30N120