


ACME 68

Φ68 Adjustable 220-240V~ Track Light



Adjustable Optic



- B Black Painted 9005
- W White Painted 9016

- RC Regency Champagne
- HB Heritage Brass



- IP Rating:** Front IP44, optional IP65
- Optics:** 15°/24°/36°/50°
- UGR:** <10
- CRI:** 98Ra
- Lifetime:** >50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K
1800-3000K(Warm Dim), 2700K - 6000K (Tunable White)

Typical Source Efficacy (lm/W): 110

Control: On/off, Mains Dim, 0/1-10V, Dali, Casambi

Binning: 2 Step MacAdams

Input: AC220-240V 50/60Hz


Output: DC 36V 200mA 8W
DC 36V 250mA 10W
DC 36V 300mA 12W

Ambient temp: -20 °C to 45 °C

Class: II


Optional accessories: Honeycomb louvre, Solite Lens, Spread Lens, Colour Filter

Material: Fine aluminium 6063A




12W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	17841	0.14
1.0	4460	0.27
1.5	1982	0.41
2.0	1115	0.55
2.5	714	0.68
3.0	496	0.82




12W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	9544	0.22
1.0	2386	0.44
1.5	1060	0.65
2.0	596	0.87
2.5	382	1.09
3.0	265	1.31



12W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	4724	0.31
1.0	1181	0.62
1.5	525	0.92
2.0	295	1.23
2.5	189	1.54
3.0	131	1.85



12W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	1171	0.47
1.0	428	0.95
1.5	190	1.42
2.0	107	1.90
2.5	68	2.37
3.0	48	2.85



Regency Champagne

A luminous pearl finish infused with soft champagne-gold undertones, Regency Champagne exudes quiet glamour and modern refinement. Its silky sheen catches the light with subtle elegance, bringing a sense of brightness, serenity, and sophistication to contemporary, minimalist, coastal, and transitional interiors. Paired with marble, glass, and gentle neutral tones, it enhances a space with warmth and polish while preserving a calm, understated luxury.



Heritage Brass

A multi-layered, hand-refined deep umber finish with delicate golden undertones and a nuanced patina that embodies Quiet Luxury. Ideal for British classic, organic modern, and bespoke residential interiors, adding a grounded, timeless elegance to marble, dark timber, and artisanal plaster palettes.



W system	lm system	optics	code
8W	648	15°	AFL6808W-TK-30N15
8W	701	24°	AFL6808W-TK-30N24
8W	655	36°	AFL6808W-TK-30N36
8W	558	50°	AFL6808W-TK-30N50



W system	lm system	optics	code
10W	787	15°	AFL6810W-TK-30N15
10W	856	24°	AFL6810W-TK-30N24
10W	817	36°	AFL6810W-TK-30N36
10W	731	50°	AFL6810W-TK-30N50



W system	lm system	optics	code
12W	897	15°	AFL6812W-TK-30N15
12W	1000	24°	AFL6812W-TK-30N24
12W	941	36°	AFL6812W-TK-30N36
12W	846	50°	AFL6812W-TK-30N50