



ACME ALABASTER

Φ57 Engine

Surface Fixed Alabaster Luna




Fixed Optic



Pearl Nickel



IP Rating:	Front IP44, optional IP65
Optics:	120°
UGR:	<10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W
Ambient temp:	-20 C to 45 C
Class:	II
Material:	Fine Aluminium 6063A + Alabaster Stone
Fire resistance test:	60 minutes
Certification:	CB/CE/UKCA/GLOBAL MARK/60-MINUNTE FIRE RESISTANCE



10W Ra98 3000K 120°

h(m)	E(lx)	D(m)
0.5	9	1.61
1.0	2	3.23
1.5	1	4.84



W system	lm system	optics	code
6W	82	120°	SFE5706W-AL-30N120
8W	105	120°	SFE5708W-AL-30N120
10W	128	120°	SFE5710W-AL-30N120