







# ACME

## Φ57 Engine Surface Fixed Light




Fixed Optic




-  -B Black Painted 9005
-  -W White Painted 9016
-  -RC Regency Champagne
-  -HB Heritage Brass

- IP Rating:** Front IP44, optional IP65
- Optics:** 15°/24°/36°/50°
- UGR:** < 10
- CRI:** 98Ra
- Lifetime:** > 50,000 hrs (L70 B10)
- CCT:** 2700K/3000K/3500K/4000K  
1800-3000K(Warm Dim), 2700K - 6000K (Tunable White)
- Typical Source**
- Efficacy (lm/W):** 110
- Control:** On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
- Binning** 2 Step MacAdams
- Input:** AC220-240V 50/60Hz
- Output:** DC 36V 150mA 6W  
DC 36V 200mA 8W  
DC 36V 250mA 10W
- Ambient temp:** -20 °C to 45 °C
- Class:** II
- Optional accessories:** Honeycomb louvre, Solite Lense, Spread Lense, Colour Filter
- Material:** Fine aluminium 6063A




10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	13172	0.14
1.0	3293	0.28
1.5	1464	0.42
2.0	823	0.56
2.5	527	0.70
3.0	366	0.84




10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	7091	0.21
1.0	1773	0.43
1.5	788	0.64
2.0	443	0.86
2.5	284	1.07
3.0	197	1.29



10W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	3820	0.31
1.0	955	0.63
1.5	424	0.94
2.0	239	1.25
2.5	153	1.57
3.0	106	1.88



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	1678	0.50
1.0	420	1.01
1.5	186	1.51
2.0	105	2.01
2.5	67	2.51
3.0	47	3.02



W system	lm system	optics	code
6W	450	15°	SFE5706W-30N15
6W	532	24°	SFE5706W-30N24
6W	523	36°	SFE5706W-30N36
6W	464	50°	SFE5706W-30N50



W system	lm system	optics	code
8W	582	15°	SFE5708W-30N15
8W	624	24°	SFE5708W-30N24
8W	661	36°	SFE5708W-30N36
8W	600	50°	SFE5708W-30N50



W system	lm system	optics	code
10W	704	15°	SFE5710W-30N15
10W	751	24°	SFE5710W-30N24
10W	814	36°	SFE5710W-30N36
10W	723	50°	SFE5710W-30N50