


# ACME ALABASTER

## Φ68 Engine

### Surface Fixed Alabaster Globe




Fixed Optic



 -RC Regency Champagne



<b>IP Rating:</b>	Front IP44, optional IP65
<b>Optics:</b>	120°
<b>UGR:</b>	<10
<b>CRI:</b>	98Ra
<b>Lifetime:</b>	>50,000 hrs (L70 B10)
<b>CCT:</b>	2700K/3000K
<b>Typical Source</b>	
<b>Efficacy (lm/W):</b>	110
<b>Control:</b>	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
<b>Binning</b>	2 Step MacAdams
<b>Input:</b>	AC220-240V 50/60Hz
<b>Output:</b>	DC 36V 200mA 8W DC 36V 250mA 10W DC 36V 300mA 12W
<b>Ambient temp:</b>	-20 °C to 45 °C
<b>Class:</b>	II
<b>Material:</b>	Fine Aluminium 6063A + Alabaster Stone



h(m)	E(lx)	D(m)
0.5	59	1.24
1.0	15	2.48
1.5	7	3.72
2.0	4	4.96

12W Ra98.3000K 120°



<b>W system</b>	<b>lm system</b>	<b>optics</b>	<b>code</b>
8W	235	120°	SFE6808W-AG-30N120
10W	286	120°	SFE6810W-AG-30N120
12W	337	120°	SFE6812W-AG-30N120