


# ACME ALABASTER

## Φ57 Engine


### Alabaster Globe Wall Light



Fixed Optic




<b>IP Rating:</b>	Front IP44, optional IP65
<b>Optics:</b>	120°
<b>UGR:</b>	<10
<b>CRI:</b>	98Ra
<b>Lifetime:</b>	>50,000 hrs (L70 B10)
<b>CCT:</b>	2700K/3000K
<b>Typical Source Efficacy (lm/W):</b>	110
<b>Control:</b>	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
<b>Binning</b>	2 Step MacAdams
<b>Input:</b>	AC220-240V 50/60Hz
<b>Output:</b>	DC 36V 150mA 6W*2 DC 36V 200mA 8W*2 DC 36V 250mA 10W*2
<b>Ambient temp:</b>	-20 °C to 45 °C
<b>Class:</b>	II
<b>Material:</b>	Fine Aluminium 6063A + Alabaster Stone
<b>Fire resistance test:</b>	60 minutes
<b>Certification:</b>	CB/CE/UKCA/GLOBAL MARK/60-MINUNTE FIRE RESISTANCE



h(m)	E(lx)	D(m)
0.5	52	1.20
1.0	13	2.40
1.5	6	3.60
2.0	3	4.80

10W Ra98 3000K 120°



W system	lm system	optics	code
6W*2	182*2	120°	WE5706WX2-AG-30N120
8W*2	235*2	120°	WE5708WX2-AG-30N120
10W*2	286*2	120°	WE5710WX2-AG-30N120