


ACME ALABASTER

Φ57 Engine

Alabaster Globe Wall Light




Fixed Optic



Pearl Nickel



IP Rating:	Front IP44, optional IP65
Optics:	120°
UGR:	<10
CRI:	98Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	2700K/3000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Mains Dim, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W*2 DC 36V 200mA 8W*2 DC 36V 250mA 10W*2
Ambient temp:	-20 °C to 45 °C
Class:	II
Material:	Fine Aluminium 6063A + Alabaster Stone
Fire resistance test:	60 minutes
Certification:	CB/CE/UKCA/GLOBAL MARK/60-MINUNTE FIRE RESISTANCE



h(m)	E(lx)	D(m)
0.5	52	1.20
1.0	13	2.40
1.5	6	3.60
2.0	3	4.80

10W Ra98 3000K 120°



W system	lm system	optics	code
6W*2	182*2	120°	WE5706WX2-AG-30N120
8W*2	235*2	120°	WE5708WX2-AG-30N120
10W*2	286*2	120°	WE5710WX2-AG-30N120