

ACME FIXED



Φ36 Engine Mini-Trim Fixed Round Downlight



CUTOUT :36mm




Fixed Optic




Accessories can be ordered separately

Light Engine



SKU : EN-36

Mini-Trim



SKU : BZ-36



CUTOUT:36

36 Commissioning Tool
for removal of 36 engine
from the bezels



SKU : 36CT

Standard




Black
Painted
9005



White
Painted
9016

IP Rating:	IP20
Optics:	24°
UGR:	<10
CRI:	92Ra
Lifetime:	>50,000 hrs (L70 B10)
CCT:	3000K/3500K
Typical Source Efficacy (lm/W):	103
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 12V 300mA 5W
Ambient temp:	-20 °C to 25 °C
Class:	III
Ceiling Thickness:	5mm-28mm
Material:	Fine aluminium 6063A
Certifications:	CE, RoHS



5W Ra92 3000K 24°

h(m)	E(lx)	D(m)
0.5	1582	0.19
1.0	396	0.38
1.5	176	0.57
2.0	99	0.76
2.5	63	0.95
3.0	44	1.14




Code example:

MFL 36 05W- 30 N 24-W B

MFL/ fixed
36 / cutout 36mm
05W / system power
30 / 3000K
N / non dim
24 / beam angle 24°
W/ white bezel
B/ black baffle



DuraGreen project:
KY Office



W system	lm system	optics	code
5W	127	24°	MFL3605W-30N24