


ACME 68

Φ68


Adjustable 220-240V~ Track Light



Adjustable Optic




Bespoke




25W Ra92 3000K 15°

h(m)	E(lx)	D(m)
0.5	39527	0.15
1.0	9882	0.30
1.5	4392	0.45
2.0	2470	0.60
2.5	1581	0.75
3.0	1098	0.90




25W Ra92 3000K 24°

h(m)	E(lx)	D(m)
0.5	20830	0.23
1.0	5207	0.45
1.5	2314	0.68
2.0	1302	0.91
2.5	833	1.14
3.0	579	1.36



25W Ra92 3000K 36°

h(m)	E(lx)	D(m)
0.5	10638	0.32
1.0	2660	0.65
1.5	1182	0.97
2.0	665	1.30
2.5	426	1.62
3.0	296	1.95



25W Ra92 3000K 50°

h(m)	E(lx)	D(m)
0.5	6403	0.47
1.0	1601	0.94
1.5	711	1.41
2.0	400	1.88
2.5	256	2.35
3.0	178	2.82

IP Rating:	IP20
Optics:	15°/24°/36°/50°
UGR:	<10
CRI:	92Ra
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 350mA 15W DC 36V 500mA 20W DC 36V 600mA 25W
Ambient temp:	-20 °C to 25 °C
Class:	II
Optional accessories:	Honeycomb, Elliptical Lens, Solite lens
Material:	structure fine aluminum 6063A
Suitable Tracks:	Global, A.A.G STUCCHI, Eutrac, PowerGEAR, ERCO
Certifications:	CE



Code example:

AATL 68 15W -30 N 15- B

AATL/ ACME 220V adjustable track light

68 / 68 engine

15W / system power

30 / 3000K

N / non dim

15/ beam angle 15°

B/ black structure



W system	lm system	optics	code
15W	1609	15°	AATL6815W-30N15
15W	1587	24°	AATL6815W-30N24
15W	1665	36°	AATL6815W-30N36
15W	1476	50°	AATL6815W-30N50



W system	lm system	optics	code
20W	2006	15°	AATL6820W-30N15
20W	2012	24°	AATL6820W-30N24
20W	2106	36°	AATL6820W-30N36
20W	1850	50°	AATL6820W-30N50



W system	lm system	optics	code
25W	1476	15°	AATL6825W-30N15
25W	2378	24°	AATL6825W-30N24
25W	2440	36°	AATL6825W-30N36
25W	2185	50°	AATL6825W-30N50