


ACME 68

Φ68

Adjustable 220-240V~ Track Light



Adjustable Optic



Bespoke



IP Rating:	IP20
Optics:	Wall Wash
UGR:	<17
CRI:	92Ra
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K/3000K/3500K/4000K
Typical Source	
Efficacy (lm/W):	145
Control:	On/off, Phase Cut, 0/1-10V, Dali, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 350mA 15W DC 36V 500mA 20W DC 36V 600mA 25W
Ambient temp:	-20 °C to 25 °C
Class:	II
Material:	structure fine aluminum 6063A
Suitable Tracks:	Global, A.A.G STUCCHI, Eutrac, PowerGEAR, ERCO
Certifications:	CE



Code example:

AATL 68 20W -30 N WW- B
AATL/ ACME 220V adjustable track light
68 / 68 engine
20W / system power
30 / 3000K
N / non dim
WW/ wall wash
B/ black structure



W system	lm system	optics	code
15W	448	Wall Wash	AATL6815W-30NWW
20W	597	Wall Wash	AATL6820W-30NWW
25W	747	Wall Wash	AATL6825W-30NWW