

ACME CURVE

Φ57 Engine

Mini-Trim Adjustable Round Downlight



CUTOUT:57mm



Adjustable Optic



Accessories can be ordered separately

Light Engine




SKU : EN-57

Mini-Trim





SKU : BZ-57

Curve Baffle



SKU : BF-57-C



Standard



Black
Painted
9005



White
Painted
9016

Curated Finishes (MOQ 20 applies)



Bright
Chrome



Regency
Champagne



Antique
Copper



Antique
Brass



Dark
Brass

IP Rating:	IP65 front
Optics:	15°/24°/36°/50°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
Typical Source Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output:	DC 36V 150mA 6W DC 36V 200mA 8W DC 36V 250mA 10W

Ambient temp: -20 °C to 25 °C


Class: III

Optional accessories: Honeycomb, Elliptical Lens, Solite lens

Ceiling Thickness: 9mm-28mm


Material: Fine aluminium 6063A

Certifications: CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MINUT FIRE RESISTANCE, CCC, BIS




10W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	13172	0.14
1.0	3293	0.28
1.5	1464	0.42
2.0	823	0.56
2.5	527	0.70
3.0	366	0.84




10W Ra98 3000K 24°

h(m)	E(lx)	D(m)
0.5	7091	0.21
1.0	1773	0.43
1.5	788	0.64
2.0	443	0.86
2.5	284	1.07
3.0	197	1.29



10W Ra98 3000K 36°

h(m)	E(lx)	D(m)
0.5	3820	0.31
1.0	955	0.63
1.5	424	0.94
2.0	239	1.25
2.5	153	1.57
3.0	106	1.88



10W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	1678	0.50
1.0	420	1.01
1.5	186	1.51
2.0	105	2.01
2.5	67	2.51
3.0	47	3.02



Code example:

AFL 57 10W- C -30 N 36-W B H

AFL/ adjustable

57 / cutout 57mm

10W / system power

C / curve baffle

30 / 3000K


N / non dim

36 / beam angle 36°

W/ white bezel

B/ black baffle

H/ Honeycomb (Optional)



DuraGreen project:

Private Residence Croydon Park Sydney



W system	lm system	optics	code
6W	450	15°	AFL5706W-C-30N15
6W	532	24°	AFL5706W-C-30N24
6W	523	36°	AFL5706W-C-30N36
6W	464	50°	AFL5706W-C-30N50



W system	lm system	optics	code
8W	582	15°	AFL5708W-C-30N15
8W	624	24°	AFL5708W-C-30N24
8W	661	36°	AFL5708W-C-30N36
8W	600	50°	AFL5708W-C-30N50



W system	lm system	optics	code
10W	704	15°	AFL5710W-C-30N15
10W	751	24°	AFL5710W-C-30N24
10W	814	36°	AFL5710W-C-30N36
10W	723	50°	AFL5710W-C-30N50