

ACME CURVE

Φ78 Engine

Mini-Trim Adjustable Round Downlight



CUTOUT :78mm



Adjustable Optic



Accessories can be ordered separately

Light Engine




SKU : EN-78

Mini-Trim





SKU : BZ-78

Curve Baffle



SKU : BF-78-C



Standard



Black Painted
9005



White Painted
9016

Curated Finishes (MOQ 20 applies)



Bright
Chrome



Regency
Champagne



Antique
Copper



Antique
Brass




Dark
Brass


IP Rating:	IP44 front
Optics:	5°/15°/24°/36°/50°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K / 3000K / 3500K / 4000K / 2700K-6000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, Phase Cut, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input:	AC220-240V 50/60Hz
Output(15°-50°):	DC 36V 200mA 8W DC 36V 250mA 10W DC 36V 300mA 12W

Ambient temp:	-20 °C to 25 °C
Class:	III
Optional accessories:	Honeycomb, Elliptical Lens, Solite lens
Ceiling Thickness:	9mm-28mm
Material:	Fine aluminium 6063A
Certifications:	CB, CE, RoHS, ERP, UKCA, GLOBAL MARK, 60-MINUT FIRE RESISTANCE, CCC, BIS IEC-62471-Photobiological-safety


*5° uses 12W micro LED; other beams use standard 36V COB.




10W Ra98 3000K 5°




12W Ra98 3000K 15°



12W Ra98 3000K 24°



12W Ra98 3000K 36°



12W Ra98 3000K 50°

h(m)	E(lx)	D(m)
0.5	43452	0.05
1.0	10863	0.10
1.5	4828	0.15
2.0	2716	0.20
2.5	1738	0.24
3.0	1207	0.29

h(m)	E(lx)	D(m)
0.5	17662	0.13
1.0	4416	0.26
1.5	1962	0.39
2.0	1104	0.52
2.5	706	0.65
3.0	491	0.78

h(m)	E(lx)	D(m)
0.5	6966	0.22
1.0	1741	0.44
1.5	774	0.65
2.0	435	0.87
2.5	279	1.09
3.0	193	1.31

h(m)	E(lx)	D(m)
0.5	3324	0.32
1.0	831	0.64
1.5	369	0.96
2.0	208	1.28
2.5	133	1.61
3.0	92	1.93

h(m)	E(lx)	D(m)
0.5	1826	0.48
1.0	456	0.95
1.5	203	1.43
2.0	114	1.91
2.5	73	2.38
3.0	51	2.86



Code example:

AFL 78 12W- C -30 N 36-W B H

AFL/ adjustable

78 / cutout 78mm

12W / system power

C / curve baffle

30 / 3000K

N / non dim

36 / beam angle 36°

W/ white bezel

B/ black baffle

H/ Honeycomb (Optional)



DuraGreen project:
Luxury Home in North London



W system	lm system	optics	code
6W	186	5°	AFL7806W-C-30N05



W system	lm system	optics	code
8W	255	5°	AFL7808W-C-30N05
8W	573	15°	AFL7808W-C-30N15
8W	548	24°	AFL7808W-C-30N24
8W	519	36°	AFL7808W-C-30N36
8W	600	50°	AFL7808W-C-30N50



W system	lm system	optics	code
10W	276	5°	AFL7810W-C-30N05
10W	699	15°	AFL7810W-C-30N15
10W	666	24°	AFL7810W-C-30N24
10W	624	36°	AFL7810W-C-30N36
10W	726	50°	AFL7810W-C-30N50



W system	lm system	optics	code
12W	822	15°	AFL7812W-C-30N15
12W	790	24°	AFL7812W-C-30N24
12W	780	36°	AFL7812W-C-30N36
12W	841	50°	AFL7812W-C-30N50