


ARTFOCUS 48V

Φ36


Adjustable 48V Track Light



Adjustable Optic




minimal track



standard track




IP Rating:	IP20
Optics:	15°/28°/36°
UGR:	<10
CRI/RF/RG/R9:	typ. 98/95/104/97
Lifetime:	50,000 hrs (L90 B10)
CCT:	2700K/3000K/3500K/2700-6000K
Typical Source	
Efficacy (lm/W):	110
Control:	On/off, 0/1-10V, Dali, Zigbee, Casambi
Binning	2 Step MacAdams
Input :	48 VDC
Output :	DC 36V 150mA 6W
Ambient temp:	-20 °C to 25 °C
Class:	III
Material:	structure fine aluminum 6063
Optional Accessories:	Honeycomb, Elliptical Lens, Solite lens




6W Ra98 3000K 15°

h(m)	E(lx)	D(m)
0.5	4937	0.14
1.0	1234	0.27
1.5	549	0.41
2.0	309	0.54
2.5	197	0.68
3.0	137	0.81



6W Ra98 3000K 28°

h(m)	E(lx)	D(m)
0.5	2848	0.25
1.0	712	0.49
1.5	316	0.74
2.0	178	0.98
2.5	114	1.23
3.0	79	1.47



6W Ra98 3000K 36°


h(m)	E(lx)	D(m)
0.5	1706	0.31
1.0	426	0.62
1.5	190	0.93
2.0	107	1.25
2.5	68	1.56
3.0	47	1.87



Code example:

TK 36 06W -30 N 15-W B

TK/ 48V track light
 36 / 36 diameter
 06W / system power
 30 / 3000K
 N / non dim
 15/ beam angle 15°
 B/ black structure



DuraGreen project:
 Steve O Art



W system	lm system	optics	code
6W	373	15°	TK3606W-30N15
6W	445	28°	TK3606W-30N28
6W	446	36°	TK3606W-30N36